

# ExpertAire R-410A LV Series Dehumidifiers

□ EFFECTIVE HUMIDITY CONTROL □ WIDE AMBIENT RANGE □ SELF-CONTAINED SYSTEM □ AIR CONDITIONING OPTION

## Data Sheet for Models LV 03-08

### SYSTEM SUMMARY *Standard & Premium Efficiency Blower Motors*

Desert Aire's ExpertAire dehumidifiers have many options to insure that they meet the requirements of each specific jobsite. This flexibility has a significant impact on the specifications of each unit, therefore details must be provided after the system is defined using customer requirements such as power, duct static pressure and unit configuration. The ratings below provide a guide to the systems specifications and should not be relied upon for submittal data. Desert Aire or its sales representative will provide a detail submittal for each jobsite including details on connection sizes, electrical ratings and capacities.

The LV Series dehumidifiers use 410A refrigerant. The performance below are based on the nominal air volumes listed and rated at the conditions specified in AHRI Standard 910, Performance rating of indoor pool dehumidifiers.

For units with remote condensers, please consult the submittal for details on line set sizing as they are impacted by horizontal and vertical distance between the dehumidifier and the remote condenser.

### SYSTEM SPECIFICATIONS

MODEL	LV 03	LV 04	LV 05	LV 06	LV 08	LV 08 Tandem
Moisture Removal Capacity (MRC) lbs./hr.*	18.0	25.1	29.8	38.2	39.2	45.0
Moisture Removal Efficiency (MRE)*	4.7	4.5	4.3	4.6	4.0	4.3
Moisture Removal Capacity (MRC) lbs./hr.**	18.0	25.1	29.8	38.2	39.2	45.0
Moisture Removal Efficiency (MRE)**	4.4	4.5	4.2	4.5	4.0	4.2
Total Cooling Capacity MBH*	43.4	60.9	73.7	95.5	100.3	110.5
Sensible Cooling Capacity MBH*	24.4	34.3	42.1	55.1	58.7	62.8
Maximum Outdoor Air (cfm)*	700	1,000	1,600	1,500	1,725	1,725
Supply Air Volume (cfm)	1,500	2,100	3,000	3,400	3,800	3,800
Approx. Power Consumption - kW* Stnd Eff Blowers	3.8	5.6	6.9	8.3	9.8	10.5
<b>BLOWER - Std. or Premium efficiency Motor available</b>						
HP @ 0.5" ESP	1.0	1.5	2.0	3.0	3.0	3.0
<b>COMPRESSOR</b>						
Nominal Tonnage	3	4	5	6	8	8
<b>OPTIONAL FEATURES</b>						
<b>Pool Water Heating</b>						
Water Heating Capacity - MBH*	54	76	91	118	124	137
Water Inlet/Outlet Size CPVC SCH 80	3/4	1	1	1-1/4	1-1/4	1-1/4
Water Flow - GPM ◆	6	8	10	12	16	16
Pressure Drop - ft. W.C. ‡	5.3	6.1	5.7	9.2	9	9
<b>Pool Water Partial Heating</b>						
Water Heating Capacity - MBH*	24.2	24.2	56.3	56.3	75.7	75.7
Water Inlet / Outlet Size CPVC SCH 80	3/4	3/4	3/4	3/4	1	1
Water Flow - GPM ◆	2	2	5	5	9	9
Pressure Drop - ft. W.C. ‡	2.3	2.3	3.9	3.9	4.8	4.8
<b>REMOTE CONDENSER</b>						
RC - Hot Gas Line Size (in.) @ 50 ft. Max. Length	5/8	5/8	7/8	7/8	1-1/8	1-1/8
RC- Liquid Line Size (in.) @ 50 ft. Max. Length	1/2	1/2	5/8	5/8	5/8	5/8

Specifications are subject to slight changes without notice.

\* AHRI Standard 910 ratings at 82°F/60% RH in air cooling mode. (95°F ambient)


\*\* AHRI Standard 910 ratings at 82°F/60% RH in water cooling mode. (85°F EWT)

‡ To convert ft. W.C. to PSI, divide by 2.31.

◆ Rated GPM at recommended max water temperature of 90°F for pools.

• Single phase for LC models 01-05.

3 phase for LC 06 model only.



N120 W18485 Freistadt Road, Germantown, WI 53022

(262) 946-7400 • Fax: (262) 946-7401

www.desert-aire.com • E-mail: info@desert-aire.com



# ExpertAire R-410A LV Series Dehumidifiers LV 03-08

## PERFORMANCE - Moisture Removal Capacity

